



FCC SDoC TEST REPORT

Xiamen RGBlink Science & Technology Co., Ltd.

Meeting Streaming Solution

Test Model: RGB20X-POE-TLY

Additional Model No.: Please Refer To Page 7

Prepared for : Xiamen RGBlink Science & Technology Co., Ltd.
Address : Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : December 12, 2022
Number of tested samples : 1
Samples number : A120922075
Date of Test : December 12, 2022 ~ December 15, 2022
Date of Report : December 16, 2022





FCC SDoC TEST REPORT FCC 47 CFR Part 15 Subpart B, Class B(SDoC), ANSI C63.4 -2014

Report Reference No. : LCSA120922075E

Date Of Issue : December 16, 2022

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure... : Full application of Harmonised standards
Partial application of Harmonised standards
Other standard testing method

Applicant's Name : Xiamen RGBlink Science & Technology Co., Ltd.

Address : Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Test Specification

Standard..... : FCC 47 CFR Part 15 Subpart B, Class B(SDoC), ANSI C63.4 -2014

Test Report Form No. : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. is acknowledged as copyright owner and source of the material. SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : Meeting Streaming Solution

Test Model : RGB20X-POE-TLY

Trade Mark..... : RGBlink

Ratings : Please Refer to Page 7

Result : Positive

Compiled by:

Cindy Nie

Cindy Nie/ File administrators

Supervised by:

Baron Wen

Baron Wen/ Technique principal

Approved by:

Gavin Liang

Gavin Liang/ Manager





FCC -- TEST REPORT

Test Report No. : LCSA120922075E

December 16, 2022

Date of issue

Test Model : RGB20X-POE-TLY

EUT..... : Meeting Streaming Solution

Applicant..... : Xiamen RGBlink Science & Technology Co., Ltd.

Address..... : Room 601A, No. 37-3 Banshang community, Building 3,
Xinke Plaza, Torch Hi-Tech Industrial Development
Zone, Xiamen, China

Telephone..... : /

Fax..... : /

Manufacturer..... : Xiamen RGBlink Science & Technology Co., Ltd.

Address..... : Room 601A, No. 37-3 Banshang community, Building 3,
Xinke Plaza, Torch Hi-Tech Industrial Development
Zone, Xiamen, China

Telephone..... : /

Fax..... : /

Factory..... : Xiamen RGBlink Science & Technology Co., Ltd.

Address..... : 5th floor, 205 Xinfeng Road, Huli District, Xiamen city,
Fujian Province

Telephone..... : /

Fax..... : /

Test Result according to the standards on page 6: **Positive**

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Revision	Issue Date	Revision content	Revised By
000	December 16, 2022	Initial Issue	/





TABLE OF CONTENTS

Test Report Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	6
1.1. Description of Standards and Results	6
2. GENERAL INFORMATION	7
2.1. Description of Device (EUT).....	7
2.2. Support equipment List	8
2.3. Description of Test Facility	8
2.4. Statement of the Measurement Uncertainty	8
2.5. Measurement Uncertainty.....	9
3. TEST RESULTS	10
3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT	10
3.2. Radiated emission Measurement.....	14
4. PHOTOGRAPH	19
5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT.....	20





1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	FCC 47 CFR Part 15 Subpart B, Class B(SDoC), ANSI C63.4 -2014	---	PASS
Radiated disturbance	FCC 47 CFR Part 15 Subpart B, Class B(SDoC), ANSI C63.4 -2014	---	PASS
N/A is an abbreviation for Not Applicable.			

Test mode:		
Mode 1	Full Load	Record
***Note: All test modes were tested, but we only recorded the worst case in this report.		





2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT	: Meeting Streaming Solution
Trade Mark	: RGBlink
Test Model	: RGB20X-POE-TLY
Additional Model No.	: RGB12X-POE-TLY, RGB12X-PNDI-TLY, RGB20X-PNDI-TLY, RGB30X-POE-TLY, RGB30X-PNDI-TLY, RGB20X-USB-TLY, RGB12X-USB-H, RGB12X-USB-V, RGB20X-USB-OL, RGB12X-POE-OL, RGB12X-PNDI-OL, RGB20X-POE-OL, RGB20X-PNDI-OL, RGB30X-POE-OL, RGB30X-PNDI-OL, RGB12X-UPAI-OL, RGB12X-UNAI-OL, RGB25X-UPAI-OL, RGB25X-UNAI-OL, RGB30X-UPAI-OL, RGB30X-UNAI-OL, RGBCTL-PTZ-BK, RGB12X-UUAI-BK, RGB12X-UPAI-WH, RGB12X-UHAI-GY, RGB12X-UNAI-WH, RGB25X-UPAI-WH, RGB25X-UNAI-WH, RGB30X-UPAI-WH, RGB30X-UNAI-WH, RGB10X-USB-BK, RGB3X-eUSB-BK, RGB10X-MEET-BK, RGBABS-2PTZ-TLY, RGB3X-6MIC-BT, mini, mini-pro, mini-mx, mini-ultra, TAO 1tiny, TAO 1mini, TAO 1mini-N, TAO 1mini- HN, TAO dot, TAO 1pro, TAO 1pro-S, TAO mx, TAO ultra, ASK nano p2p, ASK nano p2p 4K
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	: For Meeting Streaming Solution: Input: 12V $\overline{=}$ 1.5A
Highest internal frequency	: Fx \leq 108MHz





Highest internal frequency (Fx)	Highest measured frequency
Fx ≤ 1.705 MHz	30 MHz
1.705 MHz < Fx ≤ 108 MHz	1 GHz
108 MHz < Fx ≤ 500 MHz	2 GHz
500 MHz < Fx ≤ 1000 MHz	5 GHz
Fx > 1 GHz	5 x Fx up to a maximum of 40 GHz

2.2. Support equipment List

Name	Manufacturers	M/N	S/N
--	--	--	--

2.3. Description of Test Facility

Site Description

EMC Lab. : NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

2.4. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



2.5. Measurement Uncertainty

Test	Parameters	Expanded Uncertainty (Ulab)	Expanded Uncertainty (Ucispr)
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	± 2.63 dB ± 2.35 dB	± 3.8 dB ± 3.4 dB
Radiated Emission	Level accuracy (9kHz to 30MHz)	± 3.68 dB	N/A
Radiated Emission	Level accuracy (30MHz to 1000MHz)	± 3.48 dB	± 5.3 dB
Radiated Emission	Level accuracy (above 1000MHz)	± 3.90 dB	± 5.2 dB

(1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.

(2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.



3. TEST RESULTS


3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT

3.1.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	Farad	EZ	/	N/A	N/A
2	EMI Test Receiver	R&S	ESR3	102312	2022-02-18	2023-02-17
3	Artificial Mains	R&S	ENV216	101288	2022-06-16	2023-06-15
4	Pulse Limiter	R&S	ESH3-Z2	102750-NB	2022-08-17	2023-08-16

3.1.2. Block Diagram of Test Setup



3.1.3. Test Standard

Power Line Conducted Emission Limits

Frequency (MHz)			Limit (dB μ V)	
			Quasi-peak Level	Average Level
0.15	~	0.50	79	66
0.50	~	30.00	73	60

NOTE1-The lower limit shall apply at the transition frequencies.

NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

3.1.4. EUT Configuration on Test

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.





3.1.5. Operating Condition of EUT

3.1.5.1. Setup the EUT as shown on Section 3.1.2

3.1.5.2. Turn on the power of all equipments.

3.1.5.3. Let the EUT work in measuring Mode 1 and measure it.

3.1.6. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC/ANSI C63.4-2014 on Conducted Emission Measurement.

The bandwidth of the test receiver is set at 9kHz.

The frequency range from 150kHz to 30MHz is investigated

3.1.7. Test Results

PASS.

The test result please refer to the next page.



Shenzhen LCS Compliance Testing Laboratory Ltd.


Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



Test Model	RGB20X-POE-TLY	Test Mode	Mode 1
Environmental Conditions	24.5°C, 53.1% RH	Test Engineer	Hy Luo
Pol	Line	Test Voltage	AC 120V/60Hz




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1556	27.14	19.63	46.77	79.00	-32.23	QP	
2	0.1573	10.26	19.63	29.89	66.00	-36.11	AVG	
3	0.4156	24.67	19.63	44.30	79.00	-34.70	QP	
4 *	0.4201	16.45	19.63	36.08	66.00	-29.92	AVG	
5	1.3336	15.66	19.66	35.32	73.00	-37.68	QP	
6	1.3471	4.23	19.66	23.89	60.00	-36.11	AVG	
7	4.6681	16.69	19.70	36.39	73.00	-36.61	QP	
8	4.6906	4.82	19.70	24.52	60.00	-35.48	AVG	
9	9.1411	20.77	19.82	40.59	73.00	-32.41	QP	
10	9.3076	6.79	19.83	26.62	60.00	-33.38	AVG	
11	20.4721	21.48	20.18	41.66	73.00	-31.34	QP	
12	20.6701	4.91	20.17	25.08	60.00	-34.92	AVG	





Test Model	RGB20X-POE-TLY	Test Mode	Mode 1
Environmental Conditions	24.5°C, 53.1% RH	Test Engineer	Hy Luo
Pol	Neutral	Test Voltage	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1668	24.41	19.63	44.04	79.00	-34.96	QP	
2		0.1694	9.20	19.63	28.83	66.00	-37.17	AVG	
3		0.4066	24.95	19.63	44.58	79.00	-34.42	QP	
4		0.4111	16.96	19.63	36.59	66.00	-29.41	AVG	
5		4.1371	20.98	19.80	40.78	73.00	-32.22	QP	
6		4.1865	6.22	19.80	26.02	60.00	-33.98	AVG	
7	*	9.1006	24.68	19.85	44.53	73.00	-28.47	QP	
8		9.2221	10.26	19.85	30.11	60.00	-29.89	AVG	
9		15.2881	22.96	19.88	42.84	73.00	-30.16	QP	
10		15.4951	2.49	19.90	22.39	60.00	-37.61	AVG	
11		20.4181	22.10	20.19	42.29	73.00	-30.71	QP	
12		20.6701	5.27	20.17	25.44	60.00	-34.56	AVG	

Note: Pre-Scan all mode, Thus record worse case mode result in this report.







3.2. Radiated emission Measurement

3.2.1. Test Equipment

The following test equipments are used during the radiated emission measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	/	N/A	N/A
2	By-log Antenna	SCHWARZBEC K	VULB9163	9163-470	2021-09-12	2024-09-11
3	Horn Antenna	SCHWARZBEC K	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
4	EMI Test Receiver	R&S	ESR3	102311	2022-08-17	2023-08-16
5	Broadband Preamplifier	/	BP-01M18G	P190501	2022-06-16	2023-06-15

3.2.2. Block Diagram of Test Setup





3.2.3. Radiated Emission Limit

Limits for Radiated Disturbance Below 1GHz

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	50
88 ~ 216	3	150	53.5
216 ~ 960	3	200	56
960 ~ 1000	3	500	64

Remark: (1) Emission level $(\text{dB})\mu\text{V} = 20 \log$ Emission level $\mu\text{V}/\text{m}$
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Limits for Radiated Emission Above 1GHz

Frequency (MHz)	Distance (Meters)	Peak Limit ($\text{dB}\mu\text{V}/\text{m}$)	Average Limit ($\text{dB}\mu\text{V}/\text{m}$)
Above 1000	3	74	54

***Note: The lower limit applies at the transition frequency.

3.2.4. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

3.2.5. Operating Condition of EUT

3.2.5.1. Setup the EUT as shown in Section 3.2.2.

3.2.5.2. Let the EUT work in test Mode 1 and measure it.

3.2.6. Test Procedure

EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated by-log antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2014 on radiated emission measurement.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



3.2.7. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10 th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average

The frequency range from 30MHz to 1000MHz and above 1000MHz is checked.

3.2.8. Radiated Emission Noise Measurement Result


PASS.

The scanning waveforms please refer to the next page.





Test Model	RGB20X-POE-TL Y	Test Mode	Mode 1
Environmental Conditions	22.3°C, 53.2% RH	Detector Function	Quasi-peak
Pol	Vertical	Distance	3m
Test Engineer	Hy Luo	Test Voltage	AC 120V/60Hz




	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	56.59	14.62	0.64	12.53	27.79	50.00	-22.21	QP
2	148.44	29.01	1.03	8.67	38.71	53.50	-14.79	QP
3	282.99	23.71	1.30	13.36	38.37	56.00	-17.63	QP
4	425.03	23.82	1.43	15.60	40.85	56.00	-15.15	QP
5	595.13	30.10	1.50	19.15	50.75	56.00	-5.25	QP
6	744.87	21.57	1.89	19.60	43.06	56.00	-12.94	QP

Note: 1. All readings are Quasi-peak values.
 2. Measured= Reading + Antenna Factor + Cable Loss
 3. The emission that are 20db below the official limit are not reported





Test Model	RGB20X-POE-TLY	Test Mode	Mode 1
Environmental Conditions	22.3°C, 53.2% RH	Detector Function	Quasi-peak
Pol	Horizontal	Distance	3m
Test Engineer	Hy Luo	Test Voltage	AC 120V/60Hz



	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	54.64	8.77	0.63	12.55	21.95	50.00	-28.05	QP
2	148.44	21.03	1.03	8.67	30.73	53.50	-22.77	QP
3	273.23	25.38	1.29	13.15	39.82	56.00	-16.18	QP
4	446.41	23.90	1.45	15.69	41.04	56.00	-14.96	QP
5	595.13	24.67	1.50	19.15	45.32	56.00	-10.68	QP
6	744.87	24.90	1.89	19.60	46.39	56.00	-9.61	QP

- Note: 1. All readings are Quasi-peak values.
 2. Measured= Reading + Antenna Factor + Cable Loss
 3. The emission that are 20db below the official limit are not reported

Note: Pre-Scan all mode, Thus record worse case mode result in this report.

Remark: For above 1000MHz, Because the emission it too low to be reported.





4. PHOTOGRAPH



Photo of Power Line Conducted Measurement




Photo of Radiated emission Measurement





5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT



Fig. 1



Fig. 2





Fig. 3




Fig. 4





Fig. 5



Fig. 6





Fig. 7



Fig. 8






Fig. 9




Fig. 10






Fig. 11




Fig. 12



-----THE END OF TEST REPORT-----

